

DEVICE AND METHOD FOR COLLECTING MOLTEN FLY ASH

Publication number: JP2005034695

Publication date: 2005-02-10

Inventor: KIRIBAYASHI TOSHIMITSU; OZAWA SABURO;
HASHIMOTO EIJIRO; YAMADA MITSUO; IWAMIZU
TSUNEO

Applicant: KYOWA EXEO CORP

Classification:

- international: **B01D53/68; B01D46/02; B01D53/50; B01D53/81;
B01D53/68; B01D46/02; B01D53/50; B01D53/81;**
(IPC1-7): B01D46/02; B01D53/50; B01D53/68;
B01D53/81

- European:

Application number: JP20030197704 20030716

Priority number(s): JP20030197704 20030716


Report a data error here

Abstract of JP2005034695

PROBLEM TO BE SOLVED: To easily eliminate clogging of a filter cloth through backwashing.

SOLUTION: A molten fly ash collecting device is installed at the position on the downstream side of a line to emit exhaust gas generated in an ash melting furnace 2 into the atmosphere, and provided with a bag filter to collect molten fly ash contained in the exhaust gas. The filtering speed at a filter cloth of the bag filter 11 is set to be 0.4-0.7 m/min.

COPYRIGHT: (C)2005,JPO&NCIPI



Data supplied from the esp@cenet database - Worldwide

L1 ANSWER 19 OF 301 CA COPYRIGHT 2006 ACS on STN
 AN 142:200601 CA
 ED Entered STN: 03 Mar 2005
 TI Method and device for capturing melting flying ash
 IN Kiribayashi, Toshimitsu; Ozawa, Saburo; Hashimoto, Eijiro; Yamada, Mitsuo;
 Iwami, Tsuneo
 PA Kyowa Exeo Corp., Japan
 SO Jpn. Kokai Tokkyo Koho, 13 pp.
 CODEN: JKXXAF
 DT Patent
 LA Japanese
 IC ICM B01D046-02
 ICS B01D053-50; B01D053-68; B01D053-81
 CC 47-2 (Apparatus and Plant Equipment)
 FAN.CNT 1

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
JP 2005034695	A2	20050210	JP 2003-197704	20030716
PRAI JP 2003-197704		20030716		

CLASS

PATENT NO.	CLASS	PATENT FAMILY CLASSIFICATION CODES
JP 2005034695	ICM	B01D046-02
	ICS	B01D053-50; B01D053-68; B01D053-81
	IPCI	B01D0046-02 [ICM,7]; B01D0053-50 [ICS,7]; B01D0053-68 [ICS,7]; B01D0053-81 [ICS,7]
	FTERM	4D002/AA02; 4D002/AA19; 4D002/AB01; 4D002/AC10; 4D002/BA03; 4D002/BA14; 4D002/CA11; 4D002/CA13; 4D002/DA05; 4D002/DA12; 4D002/EA02; 4D002/GA01; 4D002/GB01; 4D002/GB06; 4D002/GB12; 4D002/HA06; 4D058/JA04; 4D058/MA54; 4D058/NA10; 4D058/SA20; 4D058/TA02; 4D058/UA03; 4D058/UA10

AB The method is characterized by being able to eliminate the filter clogging using reversed washing. The fly ash, with an average particle size of 3.5-7.5 μ m, from the waste gas of a combustion furnace is removed by using a bag filter. The gas flow rate is controlled at 0.4-0.7 m/min. Slaked lime of 1.5-2 times of the acid gas in the waste gas is added to the gas flow before the bag filter for neutralization.

ST device capturing melting flying ash bag filter reversed washing
 IT Filters

(bags; capturing melting flying ash from waste gas using

→ teach Fly ash
 from a combustion furnace
 has particle size 3.5-7.5 μ m
 well within applicant's claimed range
 of up to 10 μ m.